



Fan-free POS Terminals that run cool even with high quality 7" or 8" TFT LCD panel



Optional built in magnetic stripe reader (MSR).



CF card slot for optional CF memory card which allows booting from HDD or optional CFcard.

The Posiflex DT-207 and DT-208 are mini sized, fully functional, quiet FanFree POS systems, suitable for all types of applications including retail and hospitality. Although small the DT series are perfectly formed, with the efficiency of a much larger system and the DT series boasts 4 serial ports, 4 USB, 1 LAN, 1 cash drawer port and PS/2 ports for external keyboard and mouse. With the built-in programmable keyboard and touch or non-touch screen the DT series saves even more space. Built with the metal + plastic housing heat is evenly dissipated to allow the DT series to be utilized in everyday and harsher environments and the built-in UPS functionality ensures your system keeps running when others fail.

The DT series offers all these features at an affordable price, with a choice of Windows or DOS support, to make your life easier with a Posiflex system.

- CPU: AMD LX700.
- Support Microsoft WEPOS, WinCE and DOS environment.
- Compact and rugged metal housing including a storage room for HDD and optional WiFi module with external antenna.
- 4 COM ports with DC power support for peripheral devices in any industrial application.
- 256MB DDR memory standard – maximum 1GB.
- VGA memory size program by software 16 up to 254 MB.
- Built-in UPS function to support the system from intermittent power failure (battery itself is an option).
- Supports power saving mode.



Fan-free



CPU



WiFi



UPS

Posiflex Fan-Free POS Terminal DT-207/208



Function	DT-207	DT-208	DT-208 H
CPU	AMD LX-700		
System Memory	DDR SODIMM socket*1, Max 1G.		
Default Memory Size	256 MB		
Power Supply	12 VDC power adaptor		
Housing	Metal + Plastic Housing		
Programmable KB	40 Keys, Stroke Type or Flat Type		
OS support	Microsoft Windows Embedded POS (WEPOS), WIN CE and DOS		
EMI / Safty Certifications	<ul style="list-style-type: none"> · Whole system is CE, FCC class A approved · Power supply is UL, TUV approved · RoHS · WEEE 		

Display			
LCD	7" LCD panel 800 X 480	8" LCD panel 800 X 600	8" LCD panel 800 X 600
Touch Controller	N/A	N/A	PS/2
Touch Sensor	N/A	N/A	5 Wire Touch Pad
Tilt Adjustment	15°~90°		

Expansion	
Storage Device	2.5" 40 GB IDE HDD or CF memory card (Option).
CF card slot	Y(memory card only)
LAN Port	10/100 MB
Serial Port	4*DB9
PS/2 KB Port	Y
PS/2 MOUSE Port	Y
UPS Port	Y
Standard USB Port	3
CR Port	1
Power ON only control	Y
Extension Slot	Y(Mini PCI Slot for Wi-Fi module)

Environment	
Operation Condition	0°C ~ +40°C or 32°F~ +104°F
Storage Condition	-20°C ~ +60°C or -4°F~ +104°F

Options	
Customer Pole Display	PD-201(1*16 LCDM, RS-232 Only) PD-309(2*20 LCDM, 200mm pole) PD-2605(2*20 VFD, 200mm pole)
UPS Battery	2.3 AH / 12V Lead Acid battery
CF Memory Card	Optional
MSR	Optional
WiFi	Optional

** The product information and specifications are subject to change without prior notice.



Optional WLAN module supports IEEE 802.11 a/b/g and WinCE driver.



Optional customer display for integrated base mounted device PD309/U (2 x 20) LCD pole display.



Optional rear mounted device PD-201 LCD customer display.



Posiflex Technologies, Inc.
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C.
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

